IOWA DEPARTMENT OF AGRICULTURE & LAND STEWARDSHIP

Anhydrous Ammonia Facility Inspection Checklist

on of tank(s) supports, 1/3 of ta rrosion pad between tank & pie e sources of plant security in plaquid and vapor valves locked. ng, appurtenances, and pump fraks. ps on relief valves.	nk. : ce.	Imp	rove Uns	ongitude Tank I	Notes	IDALS Tag No.	Capacity of Stor	age Tanks	5	_ Da	ta Plate
rrosion pad between tank & pie e sources of plant security in pla quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.	nk. : ce.	Imp	_		Notes						
rrosion pad between tank & pie e sources of plant security in pla quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.	nk. : ce.	Imp	_		Notes						
rrosion pad between tank & pie e sources of plant security in pla quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.	nk. : ce.	Imp	rove Uns	Tank I	Notes						
rrosion pad between tank & pie e sources of plant security in pla quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.	nk. : ce.	Imp	rove Uns	Tank I	Notes						
rrosion pad between tank & pie e sources of plant security in pla quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.	ce.										
e sources of plant security in pla quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.	ce.										
quid and vapor valves locked. ng, appurtenances, and pump fr aks. ps on relief valves.											
aks. ps on relief valves.	ee					nd Applicators	Counts	1			
-				Caddies Applicators 3000s Doubles					Singles		
alves replaced within 5 years of				Nur	Nurse Tanks and Applicators Sat						Uns
actured date and documented.				22	Condition of nurse tanks paint, all valves properly identified.						
ort bulkhead; caps on connectio	ns.			Relief valves replaced within 5 years of							
ed properly.					manut	factured date ar	nd documente	d	1		1
ate bleed off system, recommen is gallons.	d =			24	Tire condition.						
has required valves, hydrostation				25	25 Condition of hitches, 2 safety chains furnished for each nurse tank.						
relief, fittings, and gauges. Remote emergency shut off valve placed				General condition of valves gauges							
e emergency snut off valve place o pump.	a			26	fitting						
flexible connections used prope	ly;			27		amped hose, re					
braided, MWP 350, and labeled						tion, installatio iner placarded a			-		-
e tank(s) and piping supported &				28		ing transfer and					
ed from physical damage.				J		llon container o					
on of storage tank(s) paint, all properly identified.				29	Container. Plumbing on double purse tanks utilizes						
e tank(s) properly marked.				30	emerg	ency shutdown		1263			
ency Information" signage in pla	ce.			31	Conne toolba	ct/disconnect in	nstructions on				
ee of ignitable materials and any				Safe	ty Equipr				Sat	Improve	Uns
als inhibiting emergency actions				32		al water tank or					
amped hose, records of seasonal ion, installation/expiration date				33		10 sec or 100 f					
nent working platform.					Protective clothing: including gloves						
nang un" rack				34		slicker or pants					
				↓						Yes	No
equipment installed and operating to manufacturer's specificati				35		acility have Nh					
last Nh3 safety training?		/	/	36							
•		<u> </u>	•		equipi	nent including	water tank or s	nower?			
		/	/	35	Does f	acility have Nh	;	3 rail unload? " signs and pro	-	3 rail unload? " signs and protective	Yes 3 rail unload? " signs and protective